# Aspire 4540/4240 Series

**Quick Guide** 

Copyright © 2009. Acer Incorporated. All Rights Reserved. Aspire 4540/4240 Series Quick Guide Original Issue: 07/2009 Changes may be made periodically to the information in this publication without obligation to notify any person of such revisions or changes. Such changes will be incorporated in new editions of this manual or supplementary documents and publications. Record the model number, serial number, purchase date and place of purchase information in the space provided below. The serial number and model number are recorded on the label affixed to your computer. All correspondence concerning your unit should include the serial number, model number and purchase information. This booklet has been reviewed for accuracy. Although Acer makes all reasonable attempts for this booklet to be printed in an accurate manner, Acer takes no responsibility for any inadvertent errors or misprints. Aceris liability with respect to this booklet is subject to any limitation of liability set out in the applicable product warranty. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronically, mechanically, by photocopy, recording or otherwise, without the prior written permission of Acer Incorporated. Aspire 4540/4240 Series Notebook PC

Model number: \_\_\_\_\_\_

Serial number: \_\_\_\_\_\_

Date of purchase: \_\_\_\_\_\_

Acer and the Acer logo are registered trademarks of Acer Incorporated. Other companies' product names or trademarks are used herein for identification purposes only and belong to their respective companies.

#### First things first

We would like to thank you for making an Acer notebook your choice for meeting your mobile computing needs.

#### Your guides

To help you use your Acer notebook, we have designed a set of guides:

First off, the Just for Starters... poster helps you get started with setting up your computer.

The Aspire Series Generic User Guide contains useful information applying to all models in the Aspire product series. It covers basic topics such as Acer's Empowering Technology, using the keyboard, audio, etc. Please understand that due to its nature, the **Generic User Guide** as well as the **AcerSystem User Guide** mentioned below will occasionally refer to functions or features which are only contained in certain models of the series, but not necessarily in the model you purchased. Such instances are marked in the text with language such as "only for certain models".

The **Quick Guide** introduces you to the basic features and functions of your new computer. For more on how your computer can help you to be more productive, please refer to the AcerSystem User Guide. This guide contains detailed information on such subjects as system utilities, data recovery, expansion options and troubleshooting. In addition it contains warranty information and the general regulations and safety notices for your notebook. It is available in Portable Document Format (PDF) and comes preloaded on your notebook. Follow these steps to access it:

1 Click on Start, All Programs, AcerSystem.

2 Click on AcerSystem User Guide.



Note: Viewing the file requires Adobe Reader. If Adobe Reader is not installed on your computer, clicking on AcerSystem User Guide will run the Adobe Reader setup program first. Follow the instructions on the screen to complete the installation. For instructions on how to use Adobe Reader, access the Help and Support menu.

#### Your Acer notebook tour

After setting up your computer as illustrated in the **Just for Starters...** poster, let us show you around your new Acer notebook.

#### Top view



#	lcon	Item	Description
1		Acer Crystal Eye webcam	Web camera for video communication. (only for certain models)
2	3	Microphone	Internal microphone for sound recording.
3		Display screen	Also called Liquid-Crystal Display (LCD), displays computer output (Configuration may vary by models).

#	Icon	Item	Description
4	Ф	Power button	Turns the computer on and off.
5	<b>&gt;</b>	HDD	Indicates when the hard disk drive is active.
	1	Num Lock	Lights up when Num Lock is activated.
	A	Caps Lock	Lights up when Caps Lock is activated.
6		Keyboard	For entering data into your computer.
7		Palmrest	Comfortable support area for your hands when you use the computer.
8	<b>*</b>	Power <sup>1</sup>	Indicates the computer's power status.
	Ē	Battery <sup>1</sup>	Indicates the computer's battery status.  1. Charging: The light shows amber when the battery is charging.  2. Fully charged: The light shows blue when in AC mode.
9		Click buttons (left, center* and right)	The left and right buttons function like the left and right mouse buttons. *The center button serves as Acer Bio-Protection fingerprint reader supporting Acer FingerNav 4-way control function (only for certain models).
10		Touchpad	Touch-sensitive pointing device which functions like a computer mouse.
11	1	Touchpad toggle	Turns the internal touchpad on and off.
12	+/-	Volume Up/ Volume Down	Increase system volume/decrease system volume.
13	Р	Programmable key	User-programmable.
		Backup key	Launches Acer Backup Management for three-step data backup.
	<u>'C</u>	Wireless LAN communication button/indicator	Enables/disables the wireless LAN function. Indicates the status of wireless LAN communication.
	*	Bluetooth communication button/indicator	Enables/disables the Bluetooth function. Indicates the status of Bluetooth communication. (only for certain models)

#	lcon	Item	Description
14		Speakers	Left and right speakers deliver stereo audio output.

1. The front panel indicators are visible even when the computer cover is closed up.

#### Hotkeys

The computer employs hotkeys or key combinations to access most of the computer's controls like screen brightness, volume output.

To activate hotkeys, press and hold the **<Fn>** key before pressing the other key in the hotkey combination.

Hotkey	lcon	Function	Description
<fn> + <f2></f2></fn>	<b>©</b>	System property	Starts System Property for displaying system information.
<fn> + <f3></f3></fn>	*	Bluetooth	Enables/disables the Bluetooth function. (only for certain models)
<fn> + <f4></f4></fn>	Z	Sleep	Puts the computer in Sleep mode.
<fn> + <f5></f5></fn>		Display toggle	Switches display output between the display screen, external monitor (if connected) and both.
<fn> + <f6></f6></fn>	*	Screen blank	Turns the display screen backlight off to save power. Press any key to return.
<fn> + <f8></f8></fn>	<b>□(/=</b> )	Speaker toggle	Turns the speakers on and off.
<fn> + &lt;▷&gt;</fn>	Ö.	Brightness up	Increases the screen brightness.
<fn> + &lt; &lt;&gt;&gt;</fn>		Brightness down	Decreases the screen brightness.
<fn> + &lt;△&gt;</fn>	<b>(</b> 1)	Volume up	Increases the sound volume (only for certain models).
<fn> + &lt;▽&gt;</fn>	<b>(</b> )	Volume down	Decreases the sound volume (only for certain models).

#### Closed front view



#	lcon	Item	Description
1	PRO	Multi-in-1 card reader	Accepts Secure Digital (SD), MultiMediaCard (MMC), Memory Stick (MS), Memory Stick Pro (MS PRO), and xD-Picture Card.
	<b>D</b>		<b>Note:</b> Push to remove/install the card. Only one card can operate at any given time.

#### Rear view



#	Item	Description
1	Ventilation slots	Enable the computer to stay cool, even after prolonged use.

#### Left view




#	lcon	Item	Description
1		DC-in jack	Connects to an AC adapter.
2	<del>2</del>	Ethernet (RJ-45) port	Connects to an Ethernet 10/100/1000-based network.
3		External display (VGA) port	Connects to a display device (e.g., external monitor, LCD projector).
4	<b>●</b> ✓•+	USB 2.0 port	Connects to USB 2.0 devices (e.g., USB mouse, USB camera).
5	HDMI	HDMI port	Supports high definition digital video connections (only for certain models).
6	<b>●</b> ✓ <b>*</b>	USB 2.0 port	Connects to USB 2.0 devices (e.g., USB mouse, USB camera).
7	SPDIF	Headphones/ speaker/line-out jack with S/PDIF support	Connects to audio line-out devices (e.g., speakers, headphones).
	100	Microphone jack	Accepts inputs from external microphones.
	( <del>+)</del>	Line-in jack	Accepts audio line-in devices (e.g., audio CD player, stereo walkman, mp3 player)

## Right view



#	Icon	Item	Description
1	<b>●</b>	USB 2.0 port	Connects to USB 2.0 devices (e.g., USB mouse, USB camera).
2		Optical drive	Internal optical drive; accepts CDs or DVDs.
3		Optical disk access indicator	Lights up when the optical drive is active.
4		Optical drive eject button	Ejects the optical disk from the drive.
5		Emergency eject hole	Ejects the optical drive tray when the computer is turned off.  Note: Insert a paper clip to the emergency eject hole to eject the optical drive tray when the computer is off.
6		Modem (RJ-11) port	Connects to a phone line.
7	ĸ	Kensington lock slot	Connects to a Kensington-compatible computer security lock.

### Base view



#	lcon	Item	Description
1	<u> </u>	Battery bay	Houses the computer's battery pack.
2		Battery release latch	Releases the battery for removal.
3		Hard disk bay	Houses the computer's hard disk (secured with screws).
4		Memory compartment	Houses the computer's main memory.
5		Battery lock	Locks the battery in position.
6		Ventilation slots and cooling fan	Enable the computer to stay cool, even after prolonged use.  Note: Do not cover or obstruct the opening of the fan.

## **Specifications**

Operating system	•	Genuine Windows 7 <sup>®</sup>
Platform	•	AMD Better By Design Program, featuring:
		<ul> <li>AMD Turion<sup>™</sup> II Ultra dual-core processor*</li> </ul>
		<ul> <li>AMD Turion<sup>™</sup> II dual-core processor*</li> </ul>
		<ul> <li>AMD Athlon<sup>™</sup> 64 II dual-core processor*</li> </ul>
		<ul> <li>AMD Mobile Sempron<sup>™</sup> processor*</li> </ul>
		AMD M880G Chipset
		<ul> <li>Acer InviLink<sup>™</sup> Nplify<sup>™</sup> 802.11b/g/Draft-N*</li> </ul>
		<ul> <li>Acer InviLink<sup>™</sup> 802.11b/g*</li> </ul>
System memory	•	Dual-Channel SDRAM support
	•	Up to 2 GB of DDR2 667 MHz memory, upgradeable to 4 GB using two soDIMM modules
Display	•	16:9 aspect ratio
	•	14" HD 1366 x 768
Graphics	•	ATI Radeon <sup>™</sup> HD 4200 Graphics*
	•	ATI Mobility Radeon <sup>™</sup> HD 4570*
Audio	•	Dolby <sup>®</sup> -optimized surround sound system with two
		built-in stereo speakers
	•	True5.1-channel surround sound output
	•	High-definition audio support
	•	S/PDIF (Sony/Philips Digital Interface) support for digital speakers
	•	Acer PureZone technology with two built-in stereo
		microphones
	•	MS-Sound compatible
Storage	•	2.5" hard disk drive
subsystem	•	Optical drive options:
		<ul> <li>Blu-ray Disc<sup>™</sup>/DVD-Super Multi double-layer drive*</li> </ul>
		<ul> <li>DVD-Super Multi double-layer drive*</li> </ul>
	•	Multi-in-1 card reader

Integrated Acer Crystal Eye webcam* Acer PureZone technology  WLAN:  Acer InviLink™ Nplify™ 802.11b/g/Draft-N* Acer InviLink™ 802.11b/g*  WPAN: Bluetooth® 2.1+Enhanced Data Rate (EDR)* LAN: Gigabit Ethernet; Wake-on-LAN ready Modem: 56K ITU V.92; Wake-on-Ring ready  Privacy control  Acer Bio-Protection fingerprint solution* BIOS user, supervisor, HDD passwords Kensington lock slot  Dimensions and weight  342 (W) x 239 (D) x 23/38.6 (H) mm (13.4 x 9.4 x 0.9/1.5 inches) 2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem  ACPI 3.0  48.8 W 4400 mAh 3-pin 65 W AC adapter* BNERGY STAR®*  Special keys and controls  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support  External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support  Microphone-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80% Non-operating: 20% to 80%	Communication	Acer Video Conference, featuring:
<ul> <li>WLAN:         <ul> <li>Acer InviLink™ Nplify™ 802.11b/g/Draft-N*</li> <li>Acer InviLink™ 802.11b/g*</li> <li>WPAN: Bluetooth® 2.1+Enhanced Data Rate (EDR)*</li> <li>LAN: Gigabit Ethernet; Wake-on-LAN ready</li> <li>Modem: 56K ITU V.92; Wake-on-Ring ready</li> </ul> </li> <li>Privacy control         <ul> <li>Acer Bio-Protection fingerprint solution*</li> <li>BIOS user, supervisor, HDD passwords</li> <li>Kensington lock slot</li> </ul> </li> <li>Dimensions and weight         <ul> <li>342 (W) x 239 (D) x 23/38.6 (H) mm</li> <li>(13.4 x 9.4 x 0.9/1.5 inches)</li> <li>2.3 kg (5.07 lbs.) with 6-cell battery pack</li> </ul> </li> <li>Power subsystem         <ul> <li>ACPI 3.0</li> <li>3-pin 65 W AC adapter*</li> <li>3-pin 90 W AC adapter*</li> <li>ENERGY STAR®*</li> </ul> </li> <li>Special keys and controls         <ul> <li>86-/87-/91-key keyboard</li> <li>Touchpad pointing device</li> </ul> </li> <li>I/O interface         <ul> <li>Acer Bio-Protection fingerprint reader</li> <li>Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)</li> <li>USB 2.0 ports</li> <li>HDMI™ port with HDCP support</li> <li>External display (VGA) port</li> <li>Headphones/speaker/line-out jack with S/PDIF support</li> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> </ul> </li> <li>Environment         <ul> <li>Temperature:</li> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> <li>Humidity (non-condensing):</li> <li>Operating: 20% to 80%<!--</th--><th></th><th><ul> <li>Integrated Acer Crystal Eye webcam*</li> </ul></th></li></ul></li></ul>		<ul> <li>Integrated Acer Crystal Eye webcam*</li> </ul>
Acer InviLink™ Nplify™ 802.11b/g/Draft-N*     Acer InviLink™ 802.11b/g*      WPAN: Bluetooth® 2.1+Enhanced Data Rate (EDR)*     LAN: Gigabit Ethernet; Wake-on-LAN ready     Modem: 56K ITU V.92; Wake-on-Ring ready  Privacy control      Acer Bio-Protection fingerprint solution*     BIOS user, supervisor, HDD passwords     Kensington lock slot  Dimensions     and weight     (13.4 x 9.4 x 0.9/1.5 inches)     2.3 kg (5.07 lbs.) with 6-cell battery pack  Power     subsystem     ACPI 3.0  ARB W 4400 mAh     3-pin 65 W AC adapter*     3-pin 90 W AC adapter*     ENERGY STAR®*  Special keys     and controls  I/O interface  Acer Bio-Protection fingerprint reader     Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)     USB 2.0 ports     HDMI™ port with HDCP support     External display (VGA) port     Headphones/speaker/line-out jack with S/PDIF support     Microphone-in jack     Line-in jack     Line-in jack     Line-in jack     Line-in jack     Ethernet (RJ-45) port     Modem (RJ-11) port     DC-in jack for AC adapter  Environment  Temperature:     Operating: 5 °C to 35 °C     Non-operating: -20 °C to 65 °C     Humidity (non-condensing):     Operating: 20% to 80%		<ul> <li>Acer PureZone technology</li> </ul>
Acer InviLink™ 802.11b/g*     WPAN: Bluetooth® 2.1+Enhanced Data Rate (EDR)*     LAN: Gigabit Ethernet; Wake-on-LAN ready     Modem: 56K ITU V.92; Wake-on-Ring ready  Privacy control  Acer Bio-Protection fingerprint solution*     BIOS user, supervisor, HDD passwords     Kensington lock slot  Dimensions     and weight  (13.4 x 9.4 x 0.9/1.5 inches)     2.3 kg (5.07 lbs.) with 6-cell battery pack  Power     subsystem  ACPI 3.0  3-pin 65 W AC adapter*     3-pin 90 W AC adapter*     5Pecial keys     and controls  I/O interface  Acer Bio-Protection fingerprint reader     Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)     USB 2.0 ports     HDMI™ port with HDCP support     External display (VGA) port     Headphones/speaker/line-out jack with S/PDIF support     Microphone-in jack     Line-in jack     Ethernet (RJ-45) port     Modem (RJ-11) port     DC-in jack for AC adapter  Environment  Temperature:     Operating: 5 °C to 35 °C     Non-operating: -20 °C to 65 °C     Humidity (non-condensing):     Operating: 20% to 80%		• WLAN:
WPAN: Bluetooth® 2.1+Enhanced Data Rate (EDR)* LAN: Gigabit Ethernet; Wake-on-LAN ready Modem: 56K ITU V.92; Wake-on-Ring ready  Privacy control Acer Bio-Protection fingerprint solution* BIOS user, supervisor, HDD passwords Kensington lock slot  Dimensions and weight (13.4 x 9.4 x 0.9/1.5 inches) 2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem ACPI 3.0 48.8 W 4400 mAh 3-pin 65 W AC adapter* 3-pin 90 W AC adapter* ENERGY STAR®*  Special keys and controls  I/O interface Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support  External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support Microphone-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%		<ul> <li>Acer InviLink<sup>™</sup> Nplify<sup>™</sup> 802.11b/g/Draft-N*</li> </ul>
Privacy control  Acer Bio-Protection fingerprint solution* BIOS user, supervisor, HDD passwords Kensington lock slot  Dimensions and weight  13.4 x 9.4 x 0.9/1.5 inches) 2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem  ACPI 3.0  48.8 W 4400 mAh 3-pin 65 W AC adapter* BINERGY STAR®*  Special keys and controls  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)  USB 2.0 ports HDMI <sup>TM</sup> port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support Microphone-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%		<ul> <li>Acer InviLink<sup>™</sup> 802.11b/g*</li> </ul>
Privacy control  Acer Bio-Protection fingerprint solution* BIOS user, supervisor, HDD passwords Kensington lock slot  Dimensions and weight  ACPI 3.0  ACPI 3.0  Subsystem  ACPI 3.0  BENERGY STAR®*  Special keys and controls  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)  USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port  Headphones/speaker/line-out jack with S/PDIF support Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Finvironment  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)  USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support  Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%		· · · · · · · · · · · · · · · · · · ·
Privacy control  Acer Bio-Protection fingerprint solution* BIOS user, supervisor, HDD passwords Kensington lock slot  Dimensions and weight  342 (W) x 239 (D) x 23/38.6 (H) mm (13.4 x 9.4 x 0.9/1.5 inches) 2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem  ACPI 3.0  48.8 W 4400 mAh 3-pin 65 W AC adapter* BENEGY STAR®*  Special keys and controls  Touchpad pointing device  I/O interface  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support  External display (VGA) port Microphone-in jack Line-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%		
BIOS user, supervisor, HDD passwords  Kensington lock slot  Dimensions and weight  342 (W) x 239 (D) x 23/38.6 (H) mm (13.4 x 9.4 x 0.9/1.5 inches)  2.3 kg (5.07 lbs.) with 6-cell battery pack  Power ACPI 3.0  subsystem  ACPI 3.0  48.8 W 4400 mAh  3-pin 65 W AC adapter*  ENERGY STAR®*  ENERGY STAR®*  Special keys and controls  Touchpad pointing device  I/O interface  Acer Bio-Protection fingerprint reader  Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)  USB 2.0 ports  HDMI™ port with HDCP support  External display (VGA) port  Headphones/speaker/line-out jack with S/PDIF support  External display (VGA) port  Headphone-in jack  Line-in jack  Ethernet (RJ-45) port  Modem (RJ-11) port  DC-in jack for AC adapter  Environment  Temperature:  Operating: 5 °C to 35 °C  Non-operating: -20 °C to 65 °C  Humidity (non-condensing):  Operating: 20% to 80%		
• Kensington lock slot  Dimensions and weight  • 342 (W) x 239 (D) x 23/38.6 (H) mm (13.4 x 9.4 x 0.9/1.5 inches) • 2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem  • ACPI 3.0 • 48.8 W 4400 mAh • 3-pin 65 W AC adapter* • ENERGY STAR®*  Special keys and controls  I/O interface  • Acer Bio-Protection fingerprint reader • Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) • USB 2.0 ports • HDMI™ port with HDCP support • External display (VGA) port • Headphones/speaker/line-out jack with S/PDIF support • Microphone-in jack • Line-in jack • Ethernet (RJ-45) port • Modem (RJ-11) port • DC-in jack for AC adapter  Environment  • Temperature: • Operating: 5 °C to 35 °C • Non-operating: -20 °C to 65 °C • Humidity (non-condensing): • Operating: 20% to 80%	Privacy control	<u> </u>
Dimensions and weight  • 342 (W) x 239 (D) x 23/38.6 (H) mm (13.4 x 9.4 x 0.9/1.5 inches) • 2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem • ACPI 3.0 • 48.8 W 4400 mAh • 3-pin 65 W AC adapter* • 3-pin 90 W AC adapter* • ENERGY STAR®*  Special keys and controls  I/O interface • Acer Bio-Protection fingerprint reader • Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) • USB 2.0 ports • HDMI™ port with HDCP support • External display (VGA) port • Headphones/speaker/line-out jack with S/PDIF support • Microphone-in jack • Line-in jack • Line-in jack • Ethernet (RJ-45) port • Modem (RJ-11) port • DC-in jack for AC adapter  Environment • Temperature: • Operating: 5 °C to 35 °C • Non-operating: -20 °C to 65 °C • Humidity (non-condensing): • Operating: 20% to 80%		
and weight  (13.4 x 9.4 x 0.9/1.5 inches)  2.3 kg (5.07 lbs.) with 6-cell battery pack  Power subsystem  48.8 W 4400 mAh 3-pin 65 W AC adapter* 5-pin 90 W AC adapter* ENERGY STAR®*  Special keys and controls  1/O interface  46.8 86-/87-/91-key keyboard Touchpad pointing device  1/O interface  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support Microphone-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%	Dimensions	
Power subsystem  • ACPI 3.0 • 48.8 W 4400 mAh • 3-pin 65 W AC adapter* • 3-pin 90 W AC adapter* • ENERGY STAR®*  Special keys and controls • Touchpad pointing device  I/O interface  • Acer Bio-Protection fingerprint reader • Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) • USB 2.0 ports • HDMI™ port with HDCP support • External display (VGA) port • Headphones/speaker/line-out jack with S/PDIF support • Microphone-in jack • Line-in jack • Ethernet (RJ-45) port • Modem (RJ-11) port • DC-in jack for AC adapter  Environment  • Temperature: • Operating: 5 °C to 35 °C • Non-operating: -20 °C to 65 °C • Humidity (non-condensing): • Operating: 20% to 80%		
subsystem  48.8 W 4400 mAh  3-pin 65 W AC adapter*  8-pin 90 W AC adapter*  ENERGY STAR®*  Special keys and controls  Acer Bio-Protection fingerprint reader  Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)  USB 2.0 ports  HDMI™ port with HDCP support  External display (VGA) port  Headphones/speaker/line-out jack with S/PDIF support  Microphone-in jack  Line-in jack  Ethernet (RJ-45) port  Modem (RJ-11) port  DC-in jack for AC adapter  Environment  Temperature:  Operating: 5 °C to 35 °C  Non-operating: -20 °C to 65 °C  Humidity (non-condensing):  Operating: 20% to 80%		• 2.3 kg (5.07 lbs.) with 6-cell battery pack
3-pin 65 W AC adapter* 3-pin 90 W AC adapter* ENERGY STAR®*  Special keys and controls  No interface  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support Microphone-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%	Power	• ACPI 3.0
• 3-pin 90 W AC adapter* • ENERGY STAR®*  Special keys and controls  • 86-/87-/91-key keyboard • Touchpad pointing device  I/O interface  • Acer Bio-Protection fingerprint reader • Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) • USB 2.0 ports • HDMI™ port with HDCP support • External display (VGA) port • Headphones/speaker/line-out jack with S/PDIF support • Microphone-in jack • Line-in jack • Line-in jack • Ethernet (RJ-45) port • Modem (RJ-11) port • DC-in jack for AC adapter  Environment  • Temperature: • Operating: 5 °C to 35 °C • Non-operating: -20 °C to 65 °C • Humidity (non-condensing): • Operating: 20% to 80%	subsystem	
• ENERGY STAR®*  Special keys and controls  • 86-/87-/91-key keyboard • Touchpad pointing device  I/O interface  • Acer Bio-Protection fingerprint reader • Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) • USB 2.0 ports • HDMI™ port with HDCP support • External display (VGA) port • Headphones/speaker/line-out jack with S/PDIF support • Microphone-in jack • Line-in jack • Line-in jack • Ethernet (RJ-45) port • Modem (RJ-11) port • DC-in jack for AC adapter  Environment  • Temperature: • Operating: 5 °C to 35 °C • Non-operating: -20 °C to 65 °C • Humidity (non-condensing): • Operating: 20% to 80%		·
special keys and controls  No interface  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support Microphone-in jack Line-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%		
and controls  • Touchpad pointing device  • Acer Bio-Protection fingerprint reader • Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) • USB 2.0 ports • HDMI™ port with HDCP support • External display (VGA) port • Headphones/speaker/line-out jack with S/PDIF support • Microphone-in jack • Line-in jack • Line-in jack • Ethernet (RJ-45) port • Modem (RJ-11) port • DC-in jack for AC adapter  Environment  • Temperature: • Operating: 5 °C to 35 °C • Non-operating: -20 °C to 65 °C • Humidity (non-condensing): • Operating: 20% to 80%		
I/O interface  Acer Bio-Protection fingerprint reader Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD) USB 2.0 ports HDMI™ port with HDCP support External display (VGA) port Headphones/speaker/line-out jack with S/PDIF support Microphone-in jack Line-in jack Line-in jack Ethernet (RJ-45) port Modem (RJ-11) port DC-in jack for AC adapter  Environment  Temperature: Operating: 5 °C to 35 °C Non-operating: -20 °C to 65 °C Humidity (non-condensing): Operating: 20% to 80%		
<ul> <li>Multi-in-1 card reader (SD/MMC/MS/MS PRO/xD)</li> <li>USB 2.0 ports</li> <li>HDMI<sup>™</sup> port with HDCP support</li> <li>External display (VGA) port</li> <li>Headphones/speaker/line-out jack with S/PDIF support</li> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Environment</li> <li>Temperature:         <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing):         <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		
<ul> <li>USB 2.0 ports</li> <li>HDMI<sup>™</sup> port with HDCP support</li> <li>External display (VGA) port</li> <li>Headphones/speaker/line-out jack with S/PDIF support</li> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Environment</li> <li>Temperature:         <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing):         <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>	I/O Interface	- · · · · · · · · · · · · · · · · · · ·
<ul> <li>HDMI<sup>™</sup> port with HDCP support</li> <li>External display (VGA) port</li> <li>Headphones/speaker/line-out jack with S/PDIF support</li> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Environment</li> <li>Temperature:         <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing):         <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		
<ul> <li>External display (VGA) port</li> <li>Headphones/speaker/line-out jack with S/PDIF support</li> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Environment</li> <li>Temperature:         <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing):         <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		·
<ul> <li>Headphones/speaker/line-out jack with S/PDIF support</li> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Environment</li> <li>Temperature:         <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing):         <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		·
<ul> <li>Microphone-in jack</li> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> </ul> Environment <ul> <li>Temperature:</li> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> <li>Humidity (non-condensing):</li> <li>Operating: 20% to 80%</li> </ul>		
<ul> <li>Line-in jack</li> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> </ul> Environment <ul> <li>Temperature:</li> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> <li>Humidity (non-condensing):</li> <li>Operating: 20% to 80%</li> </ul>		• •
<ul> <li>Ethernet (RJ-45) port</li> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Temperature:         <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing):         <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		, ,
<ul> <li>Modem (RJ-11) port</li> <li>DC-in jack for AC adapter</li> <li>Environment</li> <li>Temperature: <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing): <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		•
DC-in jack for AC adapter  Environment     Temperature:     Operating: 5 °C to 35 °C     Non-operating: -20 °C to 65 °C     Humidity (non-condensing):     Operating: 20% to 80%		• • •
<ul> <li>Environment</li> <li>Temperature: <ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> </ul> </li> <li>Humidity (non-condensing): <ul> <li>Operating: 20% to 80%</li> </ul> </li> </ul>		• • • •
<ul> <li>Operating: 5 °C to 35 °C</li> <li>Non-operating: -20 °C to 65 °C</li> <li>Humidity (non-condensing):</li> <li>Operating: 20% to 80%</li> </ul>	Environment	
<ul> <li>Non-operating: -20 °C to 65 °C</li> <li>Humidity (non-condensing):</li> <li>Operating: 20% to 80%</li> </ul>		•
<ul><li>Humidity (non-condensing):</li><li>Operating: 20% to 80%</li></ul>		
, J		
Non-operating: 20% to 80%		<ul> <li>Operating: 20% to 80%</li> </ul>
		<ul> <li>Non-operating: 20% to 80%</li> </ul>

(B)	
	Note: * Only for certain models
<b>(3)</b>	<b>Note:</b> The specifications listed above are for reference only. The exact configuration of your PC depends on the model purchased.